

AWM 20288, PVC Insulated Flat Parallel Appliance Wiring Material



UL AWM style 20288 is a flat parallel construction of two or three conductors, assembled like a type SPT cord and allowed with or without a grounding conductor. Two sources of demand drive it: it may be woven through the chain links of chain-suspended fixtures, which is the fixture-chain wiring in retail and industrial lighting, and it is also accepted for the internal wiring of appliances. Ratings run 60°C, 75°C, 80°C, 90°C or 105°C at 300Vac, over 18AWG to 12AWG solid or stranded tinned or bare copper, with 40 mils minimum average insulation and at least 60 mils of material between conductors after separation. Orders are cut and stripped to length for fixture assembly.

Our AWM 20288 Power Cable products are fully molded with a low profile ergonomic design and RoHS, REACH and PAHS compliant.

American UL AWM Power Cables

Specifications

Label	Value
Plug Cables Standard:	UL 758
Number of Wires	2 cores, 3 cores
Rated Voltage:	300V
Rated Temperature:	60°C, 75°C, 80°C, 90°C, 105°C
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40°C though plus 75°C
Approvals:	UL, cUL Certified List
Environmental Certifications:	RoHS, REACH, PAHS
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Simen Town, Yuyao

Ningbo / Zhejiang, China

315470