



IEC 60320 C19 angle American Power Cords

Plug and Connector Type: C19
American UL 3 pins IEC 60320 C19 Angle Connector plug,
American Power Supply Cords with UL Certified List.
Built to IEC 60320 C19 standards.
Rated up to 16A 125V.

Our IEC 60320 C19 angle American Power Cords products are fully molded with a low profile ergonomic design and RoHS, REACH and PAHS compliant.

American UL Power Cords

Specifications

Label	Value
Connector Standard:	IEC 60320 C19
Maximum Current rating:	16A
Maximum Voltage:	125V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
18/3	SVT, SVTO, SVTOO, HPN, SPT-2, SPT-3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW
16/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2, SPT-3, HPN
14/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3

Our other certificated products

