



American UL Power Cords

American Power Cords, NEMA 1-15P Plug to IEC 60320 C7 Connector, Type A, 2 poles Plug, UL Certified

Plug and Connector Type: A
 American UL 2 pins NEMA 1-15P plug to IEC 60320 C7 Connector, American Power Supply Cords with UL Certified List.
 Built to NEMA 1-15P, IEC 60320 C7 standards.
 Rated up to 2.5A 125V.

American Power Cords, 2.5A 125V, Type A Plug to IEC 60320 C7 Connector. The American AC Cords according to NEMA 1-15P Standards with UL certification. Non-Rewirable Plug 2 poles without Earthing Contact Moulded with Non-rewirable Flexible Cords. This American Two prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in American market. Our American Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

Specifications

Label	Value
Connector Standard:	NEMA 1-15P, IEC 60320 C7
Maximum Current rating:	2.5A
Maximum Voltage:	125V
Number of Poles and Wires:	2 poles, 2 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
2Cx18AWG, 2Cx16AWG	SPT-1, SPT-2, SPT-3
2Cx18AWG, 2Cx16AWG	NISPT-1, NISPT-2, NISPT-3
2Cx18AWG, 2Cx16AWG	HPN
2Cx18AWG, 2Cx17AWG, 2Cx16AWG	SVT, SVTO, SVTOO
2Cx18AWG, 2Cx16AWG, 2Cx14AWG	SJT, SJTO, SJTW, SJTOO, SJTOW, SJTOOW

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

**Simen Town, Yuyao
Ningbo / Zhejiang, China
315470**