



American UL Power Cords

American Power Cords, NEMA 5-15P Plug to IEC 60320 C13 Left Angle Connector, Type B, 3 poles Plug, UL Certified

Plug and Connector Type: B
American UL 3 pins NEMA 5-15P plug to IEC 60320 C13 Left Angle Connector, American Power Supply Cords with UL Certified List. Built to NEMA 5-15P, IEC 60320 C13 standards. Rated up to 10A 125V.

American Power Cords, 10A 125V, Type B Plug to IEC 60320 C13 Left Angle Connector. The American AC Cords according to NEMA 5-15P Standards with UL certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This American Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in American market. Our American Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

Specifications

Label	Value
Connector Standard:	NEMA 5-15P, IEC 60320 C13
Maximum Current rating:	10A
Maximum Voltage:	125V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3Cx18AWG, 3Cx16AWG	SPT-2, SPT-3
3Cx18AWG, 3Cx16AWG	HPN
3Cx18AWG	SVT, SVTO, SVTOO
3Cx18AWG, 3Cx16AWG, 3Cx14AWG, 3CX12AWG	SPT-3, SJT, SJTO, SJTW, SJTOO, SJTOW, SJTOOW

Our other certificated products



Tel: 0086-574-62160227 Fax: 0086-574-62615227
E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Ningbo / Zhejiang, China
315470