



American UL Power Cords

American Power Cords, IEC 60320 C14 Connector Plug, Type C14, 3 poles, UL, VDE, TUV, SAA, KC, PSE Certified

Plug and Connector Type: C14

American UL, VDE, TUV, SAA, KC, PSE 3 pins IEC 60320 C14 Connector plug, American Power Supply Cords with UL, VDE, TUV, SAA, KC, PSE Certified List.

Built to IEC 60320 C14 standards.

Rated up to 10A 125V.

American Power Cords, 10A 125V, Type C14 Plug. The American AC Cords according to IEC 60320 C14 Connector Standards with UL, VDE, TUV, SAA, KC, PSE certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This American Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in American market. Our American Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

Specifications

Label	Value
Connector Standard:	IEC 60320 C14
Maximum Current rating:	10A
Maximum Voltage:	125V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL, VDE, TUV, SAA, KC, PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
18/3	SVT, SVTO, SVTOO, HPN, SPT-2, SPT-3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW
16/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2, SPT-3, HPN
14/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3

Our other certificated products



