



## Australia SAA Power Cords

### **Australia Power Cords, AS/NZS 3112 Plug to IEC 60320 C13 Left Angle Connector, Type I, 3 poles Plug, SAA, RCM Certified**

Plug and Connector Type: I

Australia SAA, RCM 3 pins AS/NZS 3112 plug to IEC 60320 C13 Left Angle Connector, Australia Power Supply Cords with SAA, RCM Certified List.

Built to AS/NZS 3112, IEC 60320 C13 standards.

Rated up to 10A 250V.

Australia Power Cords, 10A 250V, Type I Plug to IEC 60320 C13 Left Angle Connector. The Australia AC Cords according to AS/NZS 3112 Standards with SAA, RCM certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This Australia Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in Australia market. Our Australia Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

### Specifications

Label	Value
Connector Standard:	AS/NZS 3112, IEC 60320 C13
Maximum Current rating:	10A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	SAA, RCM
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

### Available Wire Styles

Gauge/ # Conductors	Cord Type
3X0.75mm <sup>2</sup>	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.0mm <sup>2</sup>	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.5mm <sup>2</sup>	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F

### Our other certificated products



