Australia SAA Power Cords

Australia Power Cords, AS/NZS 3112 Plug to IEC 60320 C19 Connector, Type I, 3 poles Plug, SAA, RCM Certified

Plug and Connector Type: I
Australia SAA, RCM 3 pins AS/NZS 3112 plug to IEC 60320 C19 Connector, Australia Power Supply Cords with SAA, RCM Certified List. Built to AS/NZS 3112, IEC 60320 C19 standards.
Rated up to 16A 250V.
Australia Power Cords, 16A 250V, Type I Plug to IEC 60320 C19 Connector. The Australia AC Cords according to AS/NZS 3112 Standards with SAA, RCM certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This Australia Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in Australia market. Our Australia Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

E-mail Now

Specifications

Label	Value
Connector Standard:	AS/NZS 3112, IEC 60320 C19
Maximum Current rating:	16A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40°C through plus 75°C
Approvals:	SAA, RCM
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3X0.75mm²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.0mm²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.5mm²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F

Our other certificated products

Yuyao ChengBang
Tel: 0086-574-62160227 Fax: 0086-574-62615227
E-mail: sales@chinapowercords.com https://www.chinapowercords.com
Simen Town, Yuyao
Ningbo / Zhejiang, China
315470

http://www.chinapowercords.com