



## Australia SAA Power Cords

### **Australia Power Cords, AS/NZS 3112 Plug to IEC 60320 C7 Connector, Type I, 2 poles Plug, SAA, RCM Certified**

Plug and Connector Type: I

Australia SAA, RCM 2 pins AS/NZS 3112 plug to IEC 60320 C7 Connector, Australia Power Supply Cords with SAA, RCM Certified List.

Built to AS/NZS 3112, IEC 60320 C7 standards.

Rated up to 2.5A 250V.

Australia Power Cords, 2.5A 250V, Type I Plug to IEC 60320 C7 Connector. The Australia AC Cords according to AS/NZS 3112 Standards with SAA, RCM certification. Non-Rewirable Plug 2 poles without Earthing Contact Moulded with Non-rewirable Flexible Cords. This Australia Two prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in Australia market. Our Australia Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

### Specifications

Label	Value
Connector Standard:	AS/NZS 3112, IEC 60320 C7
Maximum Current rating:	2.5A
Maximum Voltage:	250V
Number of Poles and Wires:	2 poles, 2 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	SAA, RCM
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

### Available Wire Styles

Gauge/ # Conductors	Cord Type
2X0.75mm <sup>2</sup>	4V-75, DL2 4V-75, H03VVH2-F, H05VV-F
2x1.0mm <sup>2</sup>	4V-75, DL2 4V-75, H03VVH2-F, H05VV-F

### Our other certificated products

