



SAA 3 pins AS/NZS 3112 Angle Plug, Australia Power Supply Cords

Plug and Connector Type: I
Australia SAA, RCM 3 pins AS/NZS 3112 plug, Australia Power Supply Cords with SAA, RCM Certified List.
Built to AS/NZS 3112 standards.
Rated up to 10A 250V.

Our SAA 3 pins AS/NZS 3112 Angle Plug, Australia Power Supply Cords products are fully molded with a low profile ergonomic design and RoHS, REACH and PAHS compliant.

Australia SAA Power Cords

Specifications

Label	Value
Connector Standard:	AS/NZS 3112
Maximum Current rating:	10A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	SAA, RCM
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3X0.75mm ²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.0mm ²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.5mm ²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F

Our other certificated products

