Brazil Power Cords, IEC 60320 C19 Angle Connector Plug, Type C19, 3 poles, UL, VDE, TUV, SAA, KC, PSE Certified

Plug and Connector Type: C19

Brazil Power Cords, 16A 250V, Type C19 Plug. The Brazil AC Cords according to IEC 60320 C19 Angle Connector Standards with UL, VDE, TUV, SAA, KC, PSE certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This Brazil Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in Brazil market. Our Brazil Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

E-mail Now

Brazil Inmetro Power Cords

Specifications

Label	Value
Connector Standard:	IEC 60320 C19
Maximum Current rating:	16A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL, VDE, TUV, SAA, KC, PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm^2	H03VV-F, H05VV-F, H05RR-F, H05RN-F
3x0.75mm^2	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H05V2V2-F
3x1.00mm^2	H05VV-F, H05RR-F, H05RN-F, H05V2V2-F
3x1.5mm^2	H05VV-F, H05RR-F, H05RN-F, H05V2V2-F, H07RN-F

Our other certificated products

Yuyao ChengBang
Tel: 0086-574-62160227 Fax: 0086-574-62615227
E-mail: sales@chinapowercords.com https://www.chinapowercords.com

Simen Town, Yuyao
Ningbo / Zhejiang, China
315470

https://www.chinapowercords.com