



UK ASTA Power Cords

UK Power Cords, IEC 60320 C14 Connector Plug, Type C14, 3 poles, UL, VDE, TUV, SAA, KC, PSE Certified

Plug and Connector Type: C14

UK UL, VDE, TUV, SAA, KC, PSE 3 pins IEC 60320 C14 Connector plug, UK Power Supply Cords with UL, VDE, TUV, SAA, KC, PSE Certified List.

Built to IEC 60320 C14 standards.

Rated up to 3A,5A,7A,10A,13A 250V.

UK Power Cords, 3A,5A,7A,10A,13A 250V, Type C14 Plug. The UK AC Cords according to IEC 60320 C14 Connector Standards with UL, VDE, TUV, SAA, KC, PSE certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This UK Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in UK market. Our UK Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

Specifications

Label	Value
Connector Standard:	IEC 60320 C14
Maximum Current rating:	3A,5A,7A,10A,13A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL, VDE, TUV, SAA, KC, PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm ²	H03VV-F
3x0.75mm ²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H
3x1.0mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F
3x1.5mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F

Our other certificated products



