# UK Power Cords, IEC 60320 C14 Connector Plug, Type C14, 3 poles, UL, VDE, TUV, SAA, KC, PSE Certified

Plug and Connector Type: C14

UK Power Cords, 3A,5A,7A,10A,13A 250V, Type C14 Plug. The UK AC Cords according to IEC 60320 C14 Connector Standards with UL, VDE, TUV, SAA, KC, PSE certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This UK Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in UK market. Our UK Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

## E-mail Now

## UK ASTA Power Cords

## Specifications

| Label | Value |
|---|---|
| Connector Standard: | IEC 60320 C14 |
| Maximum Current rating: | 3A,5A,7A,10A,13A |
| Maximum Voltage: | 250V |
| Number of Poles and Wires: | 3 poles, 3 wires |
| Copper Conductor Material: | Oxygen free Copper (OFCU) |
| Outer Jacket Material: | PVC, Rubber, Halogen-Free, Textile braid |
| Blade Material: | Nickel coated Brass |
| Flamability Rating: | UL 94V-0 |
| Color: | black is standard but any color available |
| Temperature Rating: | minus 40C though plus 75C |
| Approvals: | UL, VDE, TUV, SAA, KC, PSE |
| Environmental Certifications: | RoHS, REACH, PAHs |
| Testing: | Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity |
| Packing: | Standard Export Carton |

## Available Wire Styles

| Gauge/ # Conductors | Cord Type |
|---|---|
| 3x0.5mm$^2$ | H03VV-F |
| 3x0.75mm$^2$ | H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H |
| 3x1.0mm$^2$ | H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F |
| 3x1.5mm$^2$ | H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F |

**Our other certificated products**

**Yuyao ChengBang**
Tel: 0086-574-62160227 Fax: 0086-574-62615227
E-mail: sales@chinapowercords.com https://www.chinapowercords.com

**Simen Town, Yuyao**
**Ningbo / Zhejiang, China**
**315470**

https://www.chinapowercords.com