



H01N2-D, H01N2-E, Rubber Insulated Sheathed Arc Welding Flexible Power Cables

Europe VDE, TUV Rubber Insulated Sheathed Arc Welding Flexible Power Cables

Our H01N2-D, H01N2-E Power Cable products are fully molded with a low profile ergonomic design and RoHS, REACH and PAHS compliant.

Europe VDE Rubber Power Cables

Specifications

Label	Value
Plug Cables Standard:	DIN EN 50525-2-82 (VDE 0285-525-2-82):2012-01; EN 50525-2-82:2011
Number of Wires	1 cores
Rated Voltage:	450V/750V
Rated Temperature:	60°C
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	VDE, TUV Certified List
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

**Simen Town, Yuyao
Ningbo / Zhejiang, China
315470**