



H05VV-F, H05VVH2-F, H05V2V2-F, H05V2V2H2-F, PVC Insulated Sheathed Flexible Power Cables

Europe VDE, TUV, Australia SAA, Korea KC, Brazil Inmetro Insulated Sheathed Flexible Power Cords

Our H05VV-F, H05VVH2-F, H05V2V2-F, H05V2V2H2-F Power Cable products are fully molded with a low profile ergonomic design and RoHS, REACH and PAHS compliant.

Europe VDE PVC Power Cables

Specifications

Label	Value
Plug Cables Standard:	DIN EN 50525-2-11, AS/NZS 60227.5, IEC 60227-5, K60227-5
Number of Wires	2 cores, 3 cores, 4 cores, 5 cores
Rated Voltage:	300V/500V
Rated Temperature:	70°C, 90°C
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	VDE, TUV, SAA, KC, INMETRO Certified List
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

**Simen Town, Yuyao
Ningbo / Zhejiang, China
315470**