



IEC 60320 Power Cords Connector

IEC Power Cords, IEC 60320 C13 Locking Connector Plug, Type C13, 3 poles, 3 wires, UL, ETL, VDE, TUV, SAA, KC, PSE Certified

Plug and Connector Type: IEC 60320 C13

The Type C13 IEC power cord is a three-prong grounded locking lead rated 10A, 13A, 15A, 125V/250V, that connects to an IEC 60320 C14 appliance inlet and will not shake loose in service. Produced to IEC 60320 C13 connector standards, it can be certified to UL, ETL, VDE, TUV, SAA, KC and PSE for North America, Europe and Asia. The molded, non-rewirable locking C13 head provides line, neutral and protective-earth contacts for safe Class I earthing, and a built-in locking latch grips the C14 inlet to guard against accidental unplugging caused by vibration or tugging, yet disengages quickly with a simple press. The matched flexible cord is offered in thermoplastic PVC or crosslinked rubber insulation. These locking IEC power cords are widely used on PCs, displays, servers, switches, routers, printers and rack power distribution units. As the manufacturer, we fully mold each locking C13 cord for durability and tailor cable length, wire gauge and jacket color to order; all cords meet RoHS and REACH requirements.

E-mail Now

Specifications

Label	Value
Connector Standard:	IEC 60320 C13
Maximum Current rating:	10A, 13A, 15A
Maximum Voltage:	125V/250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL/ETL/cULus
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm ²	H03VV-F, RVV, YZ, YZW
3x0.75mm ²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-F, RVV, YZ, YZW
3x1.0mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
3x1.5mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
3Cx18AWG	SVT, SVTO, SVTOO, HPN, SPT-2, SPT-3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW
3Cx16AWG	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2, SPT-3, HPN
3Cx14AWG	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3
3Cx12AWG	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Simen Town, Yuyao

Ningbo / Zhejiang, China
315470