




IEC 60320 Power Cords Connector

IEC Power Cords, IEC 60320 C13 Locking Connector Plug, Type C13, 3 poles, 3 wires, UL, ETL, VDE, TUV, SAA, KC, PSE Certified

Plug and Connector Type: IEC 60320 C13

IEC Power Cords, rated 10A, 13A, 15A at 125V/250V, featuring the Type C13 three-pole locking connector that mates with an IEC 60320 C14 inlet. This locking IEC AC power cord is manufactured to the IEC 60320 C13 standard and is available with UL, ETL, VDE, TUV, SAA, KC and PSE certification for worldwide markets. The non-rewirable, fully molded locking connector integrates line, neutral and earthing contacts for a secure Class I grounded connection, while its positive-lock latch clicks into the mating inlet to prevent accidental disconnection from vibration, movement or cable pull, and releases by hand without tools. It can be assembled with flexible PVC-insulated or crosslinked elastomeric rubber-insulated cables. These locking C13 cords are the reliable choice for desktop computers, monitors, servers, network switches, rack PDUs and office IT equipment where an uninterrupted connection matters. Our factory molds them with a low-profile ergonomic body and supplies custom lengths, gauges and colors; every product is RoHS and REACH compliant.

E-mail Now

Specifications

Label	Value
Connector Standard:	IEC 60320 C13
Maximum Current rating:	10A, 13A, 15A
Maximum Voltage:	125V/250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL/ETL/cULus
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm ²	H03VV-F, RVV, YZ, YZW
3x0.75mm ²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-F, RVV, YZ, YZW
3x1.0mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
3x1.5mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
3Cx18AWG	SVT, SVTO, SVTOO, HPN, SPT-2, SPT-3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW
3Cx16AWG	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2, SPT-3, HPN
3Cx14AWG	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3
3Cx12AWG	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3

Our other certified products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Simen Town, Yuyao
 Ningbo / Zhejiang, China
 315470