



### **IEC 60320 C14 Power Cords Connector**

Plug and Connector Type: C14  
IEC 60320 C14 with Europe VDE, American UL, Korea KTL, Australia SAA, Japan PSE certified approval IEC 60320 C13 Standard.

Our IEC 60320 C14 Power Cords Connector products are fully molded with a low profile ergonomic design and RoHS, REACH and PAHS compliant.

## **IEC 60320 Power Cords Connector**

### **Specifications**

Label	Value
Connector Standard:	IEC 60320 C14
Maximum Current rating:	10A
Maximum Voltage:	250V/125V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL,VDE,TUV,SAA,KC,PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

### **Available Wire Styles**

Gauge/ # Conductors	Cord Type
3x0.5mm <sup>2</sup>	H03VV-F, RVV, YZ, YZW
3x0.75mm <sup>2</sup>	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-F, RVV, YZ, YZW
3x1.0mm <sup>2</sup>	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
3x1.5mm <sup>2</sup>	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
18/3	SVT, SVTO, SVTOO, HPN, SPT-2, SPT-3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW
16/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2, SPT-3, HPN
14/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3

### **Our other certificated products**



**Ningbo Zhaozhan (Yuyao ChengBang) ELECTRICAL APPLIANCE CO.,LTD.**

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: [sales@chinapowercords.com](mailto:sales@chinapowercords.com) <https://www.chinapowercords.com>

**Simen Town, Yuyao  
Ningbo / Zhejiang, China  
315470**