



## **IEC 60320 Power Cords Connector**

### **IEC Power Cords, IEC 60320 C14 Waterproof Connector Plug, Type C14, 3 poles, UL, VDE, TUV, SAA, KC, PSE Certified**

Plug and Connector Type: C14

IEC Power Cords, 10A 250V/125V, Type C14 Plug. The IEC AC Cords according to IEC 60320 C14 Waterproof Connector Standards with UL, VDE, TUV, SAA, KC, PSE certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This IEC Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in IEC market. Our IEC Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

IEC Power Cords, 10A 250V/125V, Type C14 Plug. The IEC AC Cords according to IEC 60320 C14 Waterproof Connector Standards with UL, VDE, TUV, SAA, KC, PSE certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This IEC Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in IEC market. Our IEC Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

### **Specifications**

Label	Value
Connector Standard:	IEC 60320 C14
Maximum Current rating:	10A
Maximum Voltage:	250V/125V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL, VDE, TUV, SAA, KC, PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

### **Available Wire Styles**

Gauge/ # Conductors	Cord Type
3x0.5mm <sup>2</sup>	H03VV-F, RVV, YZ, YZW
3x0.75mm <sup>2</sup>	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-F, RVV, YZ, YZW
3x1.0mm <sup>2</sup>	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
3x1.5mm <sup>2</sup>	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
18/3	SVT, SVTO, SVTOO, HPN, SPT-2, SPT-3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW
16/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2, SPT-3, HPN

**Our other certificated products**



**Yuyao ChengBang**

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: [sales@chinapowercords.com](mailto:sales@chinapowercords.com) <https://www.chinapowercords.com>

**Simen Town, Yuyao  
Ningbo / Zhejiang, China  
315470**