



IEC 60320 Power Cords Connector

IEC 60320 C14 Plug to C15 Connector Hot Condition Power Cord, 10A 250V/125V, UL, ETL, VDE, TUV, CE, SAA, KC, PSE Certified

Plug and Connector Type: C14

IEC Power Cords, 10A 250V/125V, C14 plug to C15 hot condition connector. The C14 plug goes into a C13 outlet, the C15 connector into the C16 inlet of an appliance that runs hot: kettles, urns, grills and laboratory ovens. The C15 body is rated to 120 degrees C at the contact, so the coupler does not soften. UL, ETL, VDE, TUV, CE, SAA, KC, PSE approvals, three core copper, earth contact, black or white jacket.

E-mail Now

Specifications

Label	Value
Connector Standard:	C14
Maximum Current rating:	10A
Maximum Voltage:	250V/125V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40°C though plus 75°C
Approvals:	UL/ETL/VDE/TUV/CE/SAA/KC/PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm ²	H03VV-F, RVV, YZ, YZW
3x0.75mm ²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-F, RVV, YZ, YZW
3x1.0mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
3x1.5mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
18/3	SVT, SVTO, SVTOO, HPN, SPT-2, SPT-3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW
16/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2, SPT-3, HPN
14/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com> 315470

Simen Town, Yuyao

Ningbo / Zhejiang, China