



IEC 60320 Power Cords **Connector**

IEC 60320 C14 Plug to C19 Connector PDU Power Cord, 15A 250V/125V, UL, ETL, VDE, TUV, CE, SAA, KC, PSE Certified

Plug and Connector Type: C14

IEC Power Cords, 15A 250V/125V, C14 plug to C19 connector. Feeds a C20 inlet on a blade enclosure, large server, UPS or rack PDU from a C13 outlet or a C14 outlet strip. Moulded to IEC 60320 with UL, ETL, VDE, TUV, CE, SAA, KC, PSE approvals, three core copper, earth contact, black or white jacket, lengths cut to order. The other pairings are listed on the [PDU power cords](#) page.

E-mail Now

Specifications

Label	Value
Connector Standard:	C14
Maximum Current rating:	15A
Maximum Voltage:	250V/125V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40°C though plus 75°C
Approvals:	UL/ETL/VDE/TUV/CE/SAA/KC/PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm ²	H03VV-F, RVV, YZ, YZW
3x0.75mm ²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-F, RVV, YZ, YZW
3x1.0mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
3x1.5mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
18/3	SVT, SVTO, SVTOO, HPN, SPT-2, SPT-3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW
16/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2, SPT-3, HPN
14/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com> 315470

Simen Town, Yuyao

Ningbo / Zhejiang, China