



IEC 60320 C14 Plug to C7 Connector Figure-8 Power Cord, 2.5A 250V, UL, ETL, VDE, TUV, CE, SAA, KC, PSE Certified

Plug and Connector Type: C14

IEC Power Cords, 2.5A 250V, C14 plug to C7 figure-8 connector. Feeds a C8 inlet on a switch, router, NAS or small power supply from a C13 outlet on a PDU.

Two core cable, no earth contact, UL, ETL, VDE, TUV, CE, SAA, KC, PSE approvals, black or white jacket.

IEC 60320 Power Cords Connector

E-mail Now

Specifications

Label	Value
Connector Standard:	C14
Maximum Current rating:	2.5A
Maximum Voltage:	250V
Number of Poles and Wires:	2 poles, 2 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40°C though plus 75°C
Approvals:	UL/ETL/VDE/TUV/CE/SAA/KC/PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
2x0.5mm ²	H03VV-F, H03VVH2-F
2x0.75mm ²	H03VV-F, H03VVH2-F, H05VV-F, H05VVH2-F, H05RR-F, H05RN-F, H03RT-H, H05Z1Z1-F, H05Z1Z1H2-F
2x1.0mm ²	H05VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H, H05Z1Z1-F, H05Z1Z1H2-F

Our other certificated products



