



IEC 60320 Power Cords Connector

IEC Power Cords, IEC 60320 C19 Connector Plug, Type C19, 3 poles, UL, VDE, TUV, SAA, KC, PSE Certified

Plug and Connector Type: C19

IEC Power Cords, 16A 250V/125V, Type C19 Plug. The IEC AC Cords according to IEC 60320 C19 Connector Standards with UL, VDE, TUV, SAA, KC, PSE certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This IEC Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in IEC market. Our IEC Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

IEC Power Cords, 16A 250V/125V, Type C19 Plug. The IEC AC Cords according to IEC 60320 C19 Connector Standards with UL, VDE, TUV, SAA, KC, PSE certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This IEC Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in IEC market. Our IEC Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

Specifications

Label	Value
Connector Standard:	IEC 60320 C19
Maximum Current rating:	16A
Maximum Voltage:	250V/125V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL, VDE, TUV, SAA, KC, PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm ²	H03VV-F, RVV, YZ, YZW
3x0.75mm ²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-F, RVV, YZ, YZW
3x1.0mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
3x1.5mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F, RVV, YZ, YZW
18/3	SVT, SVTO, SVTOO, HPN, SPT-2, SPT-3, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW
16/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-2, SPT-3, HPN
14/3	SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SPT-3

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Simen Town, Yuyao
Ningbo / Zhejiang, China
315470