India Power Cords, IS 1293 Plug to IEC 60320 C13 Left Angle Connector, Type M, 3 poles Plug

Plug and Connector Type: M
India BIS 3 pins IS 1293 plug to IEC 60320 C13 Left Angle Connector, India Power Supply Cords according to BIS standards.
Built to IS 1293, IEC 60320 C13 standards.
Rated up to 10A 250V.
India Power Cords, 10A 250V, Type M Plug to IEC 60320 C13 Left Angle Connector. The India AC Cords according to IS 1293 Standards. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This India Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in India market. Our India Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

India BIS Power Cords

E-mail Now

Specifications

Label	Value
Connector Standard:	IS 1293, IEC 60320 C13
Maximum Current rating:	10A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40°C through plus 75°C
Approvals:	According BIS Standards
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm²	H03VV-F
3x0.75mm²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H
3x1.0mm²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F
3x1.5mm²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F

Our other certificated products

Yuyao ChengBang
Tel: 0086-574-62160227 Fax: 0086-574-62615227
E-mail: sales@chinapowercords.com https://www.chinapowercords.com
Simen Town, Yuyao
Ningbo / Zhejiang, China
315470

http://www.chinapowercords.com