



India Power Cords, IS 1293 Plug to IEC 60320 C7 Connector, Type D, 3 poles Plug

Plug and Connector Type: D
India BIS 3 pins IS 1293 plug to IEC 60320 C7 Connector, India Power Supply Cords according to BIS standards.
Built to IS 1293, IEC 60320 C7 standards.
Rated up to 2.5A 250V.

India Power Cords, 2.5A 250V, Type D Plug to IEC 60320 C7 Connector. The India AC Cords according to IS 1293 Standards. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This India Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in India market. Our India Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

India BIS Power Cords

E-mail Now

Specifications

Label	Value
Connector Standard:	IS 1293, IEC 60320 C7
Maximum Current rating:	2.5A
Maximum Voltage:	250V
Number of Poles and Wires:	2 poles, 2 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	According BIS Standards
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
2x0.5mm ²	H03VV-F, H03VVH2-F
2x0.75mm ²	H03VV-F, H03VVH2-F, H05VV-F, H05VVH2-F, H05RR-F, H05RN-F, H03RT-H
2x1.0mm ²	H05VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H
2x1.5mm ²	H05VV-F, H05VV-F, H05RR-F, H05RN-F, H07RN-F, H03RT-H

Our other certificated products



Tel: 0086-574-62160227 Fax: 0086-574-62615227
E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

**Simen Town, Yuyao
Ningbo / Zhejiang, China
315470**