



**Korea Power Cords, KSC 8305 Plug, Type E,F, 2 poles, KC Certified**

Plug and Connector Type: E,F  
Korea KC 2 pins KSC 8305 plug, Korea Power Supply Cords with KC Certified List.  
Built to KSC8305 standards.  
Rated up to 16A 250V.

Korea Power Cords, 16A 250V, Type E,F Plug. The Korea AC Cords according to KSC 8305 Standards with KC certification. Non-Rewirable Plug 2 poles without Earthing Contact Moulded with Non-rewirable Flexible Cords. This Korea Two prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in Korea market. Our Korea Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

**Korean KC Power Cords**

**E-mail Now**

**Specifications**

| Label                         | Value                                                                      |
|-------------------------------|----------------------------------------------------------------------------|
| Connector Standard:           | KSC8305                                                                    |
| Maximum Current rating:       | 16A                                                                        |
| Maximum Voltage:              | 250V                                                                       |
| Number of Poles and Wires:    | 3 poles, 3 wires                                                           |
| Copper Conductor Material:    | Oxygen free Copper (OFCU)                                                  |
| Outer Jacket Material:        | PVC, Rubber, Halogen-Free, Textile braid                                   |
| Blade Material:               | Nickel coated Brass                                                        |
| Flamability Rating:           | UL 94V-0                                                                   |
| Color:                        | black is standard but any color available                                  |
| Temperature Rating:           | minus 40C though plus 75C                                                  |
| Approvals:                    | KC                                                                         |
| Environmental Certifications: | RoHS, REACH, PAHs                                                          |
| Testing:                      | Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity |
| Packing:                      | Standard Export Carton                                                     |

**Available Wire Styles**

| Gauge/ # Conductors   | Cord Type                                                         |
|-----------------------|-------------------------------------------------------------------|
| 2x0.5mm <sup>2</sup>  | H03VV-F, H03VVH2-F                                                |
| 2x0.75mm <sup>2</sup> | H03VV-F, H03VVH2-F, H05VV-F, H05VVH2-F, H05RR-F, H05RN-F, H03RT-H |
| 2x1.0mm <sup>2</sup>  | H05VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H                       |
| 2x1.5mm <sup>2</sup>  | H05VV-F, H05VV-F, H05RR-F, H05RN-F, H07RN-F, H03RT-H              |

**Our other certificated products**



Tel: 0086-574-62160227 Fax: 0086-574-62615227  
E-mail: [sales@chinapowercords.com](mailto:sales@chinapowercords.com) <https://www.chinapowercords.com>

**Simen Town, Yuyao  
Ningbo / Zhejiang, China  
315470**