

Malaysia Power Cords, MS 589 Plug to IEC 60320 C7 Connector, Type G, SIRIM Certified

Plug and Connector Type: G
Malaysia SIRIM 3 pins MS 589 plug to IEC 60320 C7 Connector, Malaysia Power Supply Cords with SIRIM Certified List.
Built to MS 589, IEC 60320 C7 standards.
Rated up to 3A, 5A, 7A, 10A, 13A 250V.
Malaysia MS 589 plug to IEC 60320 C7 figure-8 connector, SIRIM certified 13 A plug with 3 A fuse on 2-core cable, for double-insulated appliances.

E-mail Now

Malaysia SIRIM Power Cords

Specifications

Label	Value
Connector Standard:	MS 589, IEC 60320 C7
Maximum Current rating:	3A, 5A, 7A, 10A, 13A
Maximum Voltage:	250V
Number of Poles and Wires:	2 poles, 2 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40°C through plus 75°C
Approvals:	SIRIM
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
2x0.5mm²	H03VV-F, H03VVH2-F
2x0.75mm²	H03VV-F, H03VVH2-F, H05VV-F, H05VVH2-F, H05RR-F, H05RN-F, H03RT-H
2x1.0mm²	H05VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H
2x1.5mm²	H05VV-F, H05VV-F, H05RR-F, H05RN-F, H07RN-F, H03RT-H
3x0.5mm²	H03VV-F
3x0.75mm²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H
3x1.0mm²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F
3x1.5mm²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F

Our other certificated products

Yuyao ChengBang
Tel: 0086-574-62160227 Fax: 0086-574-62615227
E-mail: sales@chinapowercords.com https://www.chinapowercords.com
Simen Town, Yuyao
Ningbo / Zhejiang, China
315470

https://www.chinapowercords.com