



American UL Power Cords

American Power Cord NEMA 10-50P Heavy-Duty appliance Male Plug, 50A 125V/250V

Plug and Connector Type: NEMA 10-50P

American UL/ETL/cULus 3 pins NEMA 10-50P plug, American Power Supply Cords with UL/ETL/cULus Certified List.

Built to NEMA 5-20P CSA CAN/CSA-22.2 No.21-95 standards.

Rated up to 50A 125V/250V.

American power cord NEMA 10-50P Heavy-Duty appliance Male Plug is rated for 50A 125V/250V.

This American AC cord is manufactured in accordance with NEMA 10-50P standards and holds UL, ETL and cULus certifications.

It features a non-rewirable 3 prong 2 poles 3 wires molded plug With Earthing Contact (Grounded), permanently bonded to a flexible non-rewirable cord.

For general applications, this American power cord Heavy-Duty appliance supports two flexible cable options for the North American and Canadian markets: flexible cables with thermoplastic PVC insulation, and flexible cables with crosslinked elastomeric rubber insulation.

Both the power plug and cable are made of eco-friendly materials and are fully compliant with RoHS, REACH, PAHs and Prop 65 requirements. The American cords support fully customizable lengths, standard black/white finishes and custom Pantone colors. All NEMA 10-50P American power cords are widely applied to small home appliances and consumer electronics.

E-mail Now

Specifications

Label	Value
Connector Standard:	NEMA 5-20P CSA CAN/CSA-22.2 No.21-95
Maximum Current rating:	50A
Maximum Voltage:	125V/250V
Number of Poles and Wires:	2P3W
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL/ETL/cULus
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3Cx10AWG	SRDT
3Cx8AWG	SRDT, ST, STW, STO, STOW, STOO, STOOW
3Cx6AWG	SRDT, ST, STW, STO, STOW, STOO, STOOW
2Cx6AWG+1Cx8AWG	SRDT

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Simen Town, Yuyao

Ningbo / Zhejiang, China
315470