



## **American UL Power Cords**

### **American Power Cord NEMA 14-50P Rewireable Ergonomic Male Plug, 50A 125V/250V**

Plug and Connector Type: NEMA 14-50P

American UL/ETL/cULus 4 pins NEMA 14-50P plug, American Power Supply Cords with UL/ETL/cULus Certified List.

Built to NEMA 5-20P CSA CAN/CSA-22.2 No.21-95 standards.

Rated up to 50A 125V/250V.

American power cord NEMA 14-50P Rewireable Ergonomic Male Plug is rated for 50A 125V/250V.

This American AC cord is manufactured in accordance with NEMA 14-50P standards and holds UL, ETL and cULus certifications.

It features a non-rewirable 4 prong 3 poles 4 wires molded plug With Earthing Contact (Grounded), permanently bonded to a flexible non-rewirable cord.

For general applications, this American power cord Rewireable Ergonomic supports two flexible cable options for the North American and Canadian markets: flexible cables with thermoplastic PVC insulation, and flexible cables with crosslinked elastomeric rubber insulation.

Both the power plug and cable are made of eco-friendly materials and are fully compliant with RoHS, REACH, PAHs and Prop 65 requirements. The American cords support fully customizable lengths, standard black/white finishes and custom Pantone colors. All NEMA 14-50P American power cords are widely applied to small home appliances and consumer electronics.

### **E-mail Now**

#### **Specifications**

| Label                         | Value                                                                      |
|-------------------------------|----------------------------------------------------------------------------|
| Connector Standard:           | NEMA 5-20P CSA CAN/CSA-22.2 No.21-95                                       |
| Maximum Current rating:       | 50A                                                                        |
| Maximum Voltage:              | 125V/250V                                                                  |
| Number of Poles and Wires:    | 3P4W                                                                       |
| Copper Conductor Material:    | Oxygen free Copper (OFCU)                                                  |
| Outer Jacket Material:        | PVC, Rubber, Halogen-Free, Textile braid                                   |
| Blade Material:               | Nickel coated Brass                                                        |
| Flamability Rating:           | UL 94V-0                                                                   |
| Color:                        | black is standard but any color available                                  |
| Temperature Rating:           | minus 40C though plus 75C                                                  |
| Approvals:                    | UL/ETL/cULus                                                               |
| Environmental Certifications: | RoHS, REACH, PAHs                                                          |
| Testing:                      | Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity |
| Packing:                      | Standard Export Carton                                                     |

#### **Available Wire Styles**

| Gauge/ # Conductors | Cord Type                       |
|---------------------|---------------------------------|
| 2Cx6AWG+1Cx8AWG     | ST, STW, STO, STOW, STOO, STOOW |

#### **Our other certificated products**



#### **Yuyao ChengBang**

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: [sales@chinapowercords.com](mailto:sales@chinapowercords.com) <https://www.chinapowercords.com>

Simen Town, Yuyao

Ningbo / Zhejiang, China  
315470