



American UL Power Cords

American Power Cord NEMA 15-50R Heavy Duty Female Receptacle, 50A 3 PH/250V

Plug and Connector Type: NEMA 15-50R

American UL/ETL/cULus 4 pins NEMA 15-50R plug, American Power Supply Cords with UL/ETL/cULus Certified List.

Built to NEMA 1-15P CSA CAN/CSA-22.2 No.21-95 standards.

Rated up to 50A 3 PH/250V.

American power cord NEMA 15-50R Heavy Duty Female Receptacle is rated for 50A 3 PH/250V.

This American AC cord is manufactured in accordance with NEMA 15-50R standards and holds UL, ETL and cULus certifications.

It features a non-rewirable 4 prong 3 poles 4 wires molded plug With Earthing Contact (Grounded), permanently bonded to a flexible non-rewirable cord. For general applications, this American power cord Heavy Duty supports two flexible cable options for the North American and Canadian markets: flexible cables with thermoplastic PVC insulation, and flexible cables with crosslinked elastomeric rubber insulation.

Both the power plug and cable are made of eco-friendly materials and are fully compliant with RoHS, REACH, PAHs and Prop 65 requirements. The American cords support fully customizable lengths, standard black/white finishes and custom Pantone colors. All NEMA 15-50R American power cords are widely applied to small home appliances and consumer electronics.

E-mail Now

Specifications

Label	Value
Connector Standard:	NEMA 1-15P CSA CAN/CSA-22.2 No.21-95
Maximum Current rating:	50A
Maximum Voltage:	3 PH/250V
Number of Poles and Wires:	3P4W
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL/ETL/cULus
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
4Cx8AWG	SRDT/DRT
3Cx6AWG+1Cx8AWG	ST, STW, STO, STOW, STOO, STOOW
4Cx6AWG	SRDT/DRT, ST, STW, STO, STOW, STOO, STOOW

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Simen Town, Yuyao
Ningbo / Zhejiang, China
315470