



### **NEMA L14-30P to NEMA 6-50R Welder Power Extension Cords**

30 Amp to 50 Amp 125V/250V for Welder Power Extension Cords

NEMA L14-30P to NEMA 6-50R Welder Power Extension Cords, Welder Power Extension Cords, 30 Amp NEMA L14-30P to 50 Amp NEMA 6-50R, Twist Locking Plug, 125V/250V, use for Dryer Power Extension Cords, Welder Power Extension Cord Sets: with UL cUL, ETL Certified, NEMA L14-30P Male Plug to NEMA 6-50R Female Receptacle \$pkey

## **Welder Power Extension Cords**

### **Specifications**

Label	Value
Plug / Connector Standard:	NEMA L14-30P to NEMA 6-50R
Maximum Current rating:	30 Amp to 50 Amp
Maximum Voltage:	125V/250V
Number of Poles and Wires:	4 prong to 3 prong
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL / eTL Certified List
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

### **Our other certificated products**



**Yuyao ChengBang**

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: [sales@chinapowercords.com](mailto:sales@chinapowercords.com) <https://www.chinapowercords.com>

**Simen Town, Yuyao  
Ningbo / Zhejiang, China  
315470**