



### **NEMA L21-30R Twist Locking Power Cord - 30A 3PH Y/120V/208V 4P5W, Ring Rib UL/ETL/cULus Certified**

Plug and Connector Type: NEMA L21-30R

NEMA L21-30R Twist Locking Power Cord - 30A 3PH Y/120V/208V 4P5W, Ring Rib UL/ETL/cULus Certified

NEMA L21-30R twist locking power cord features a 30A 3PH Y/120V/208V rating with 5 prong Female Receptacle 4 poles 5 wires configuration and Ring Rib grip for secure handling. This NEMA L21-30R twist locking Female Receptacle housing is constructed from flame-retardant, impact-proof material. And all plug prongs are made of 100% copper to deliver superior electrical conductivity and enhanced operational safety. This twist locking plug/connector and power cable with UL, ETL and cULus certified per Standard Designation: UL817 after strict dielectric, continuity and polarity testing. The twist locking power cords mechanism avoids accidental disconnection, ideal for commercial & industrial uses: RV, EV, marine yacht shore power, server racks, medical devices, power tools, indoor/outdoor events, generator adapter cord sets and construction sites. Custom lengths and cables specification can be customized for varied installation. Our NEMA L21-30R twisted locking power cord fully meets global eco regulations including RoHS, REACH, PAHs and California Prop65 standards.

## **American Twist Locking Power Cords**

**E-mail Now**

### **Specifications**

| Label                         | Value                                                                      |
|-------------------------------|----------------------------------------------------------------------------|
| Connector Standard:           | NEMA L21-30R                                                               |
| Maximum Current rating:       | 30A                                                                        |
| Maximum Voltage:              | 3PH Y/120V/208V                                                            |
| Number of Poles and Wires:    | 5 prong 4 poles 5 wires                                                    |
| Copper Conductor Material:    | Oxygen free Copper (OFCU)                                                  |
| Outer Jacket Material:        | PVC, Rubber, Halogen-Free, Textile braid                                   |
| Blade Material:               | Nickel coated Brass                                                        |
| Flamability Rating:           | UL 94V-0                                                                   |
| Color:                        | black is standard but any color available                                  |
| Temperature Rating:           | minus 40C though plus 75C                                                  |
| Approvals:                    | UL/ETL/cULus                                                               |
| Environmental Certifications: | RoHS, REACH, PAHs                                                          |
| Testing:                      | Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity |
| Packing:                      | Standard Export Carton                                                     |

### **Available Wire Styles**

| Gauge/ # Conductors | Cord Type                                                                                                                 |
|---------------------|---------------------------------------------------------------------------------------------------------------------------|
| 5Cx14AWG            | SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO, SOOW |
| 5Cx12AWG            | SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO, SOOW |
| 5Cx10AWG            | SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW, STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO, SOOW |

### **Our other certificated products**



### **Yuyao ChengBang**

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: [sales@chinapowercords.com](mailto:sales@chinapowercords.com) <https://www.chinapowercords.com>

Simen Town, Yuyao  
Ningbo / Zhejiang, China  
315470