



American Twist Locking Power Cords

NEMA L6-20P Twist Locking Power Cord - 20A 250V 2P3W, Vertical Rib UL/ETL/cULus Certified

Plug and Connector Type: NEMA L6-20P

NEMA L6-20P Twist Locking Power Cord - 20A 250V 2P3W, Vertical Rib

UL/ETL/cULus Certified

NEMA L6-20P twist locking power cord features a 20A 250V rating with 3 prong Male Plug 2 poles 3 wires configuration and Vertical Rib grip for secure handling. This NEMA L6-20P twist locking Male Plug housing is constructed from flame-retardant, impact-proof material. And all plug prongs are made of 100% copper to deliver superior electrical conductivity and enhanced operational safety. This twist locking plug/connector and power cable with UL, ETL and cULus certified per Standard Designation: UL817 after strict dielectric, continuity and polarity testing. The twist locking power cords mechanism avoids accidental disconnection, ideal for commercial & industrial uses: RV, EV, marine yacht shore power, server racks, medical devices, power tools, indoor/outdoor events, generator adapter cord sets and construction sites. Custom lengths and cables specification can be customized for varied installation. Our NEMA L6-20P twisted locking power cord fully meets global eco regulations including RoHS, REACH, PAHs and California Prop65 standards.

E-mail Now

Specifications

Label	Value
Connector Standard:	NEMA L6-20P
Maximum Current rating:	20A
Maximum Voltage:	250V
Number of Poles and Wires:	3 prong 2 poles 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL/ETL/cULus
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3Cx18AWG	SJ, SJO, SJOW, SJO, SJOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, ST, STW, STO, STOW, STOO, STOOW
3Cx16AWG	SJ, SJO, SJOW, SJO, SJOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, ST, STW, STO, STOW, STOO, STOOW
3Cx14AWG	SJ, SJO, SJOW, SJO, SJOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, ST, STW, STO, STOW, STOO, STOOW
3Cx12AWG	SJ, SJO, SJOW, SJO, SJOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, ST, STW, STO, STOW, STOO, STOOW

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Simen Town, Yuyao
 Ningbo / Zhejiang, China
 315470