



NEMA L6-20R twist locking power cord features a 20A 250V rating with 3 prong Female Receptacle 2 poles 3 wires configuration and Ring Rib grip for secure handling. This NEMA L6-20R twist locking Female Receptacle housing is constructed from flame-retardant, impact-proof material. And all plug prongs are made of 100% copper to deliver superior electrical conductivity and enhanced operational safety. This twist locking plug/connector and power cable with UL, ETL and cULus certified per Standard Designation: UL817 after strict dielectric, continuity and polarity testing. The twist locking power cords mechanism avoids accidental disconnection, ideal for commercial & industrial uses: RV, EV, marine yacht shore power, server racks, medical devices, power tools, indoor/outdoor events, generator adapter cord sets and construction sites. Custom lengths and cables specification can be customized for varied installation. Our NEMA L6-20R twisted locking power cord fully meets global eco regulations including RoHS, REACH, PAHs and California Prop65 standards.

E-mail Now

Gauge/ # Conductors	Cord Type
3Cx16AWG	SJ, SJO, SJOW, SJOO, SJOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, ST, STW, STO, STOW, STOO, STOOW
3Cx14AWG	SJ, SJO, SJOW, SJOO, SJOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, ST, STW, STO, STOW, STOO, STOOW
3Cx12AWG	SJ, SJO, SJOW, SJOO, SJOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, ST, STW, STO, STOW, STOO, STOOW

UL DVE AIA UC PS E SABS KEMA SP KEMA EAC ÖVE Y N NF S FI D

Simen Town, Yuyao
Ningbo / Zhejiang, China
315470