



American Twist Locking Power Cords

**NEMA L7-15P Twist Locking Power Cord - 15A 277V/AC 2P3W.,
Waterproof Ring Rib UL/ETL/cULus Certified**

Plug and Connector Type: NEMA L7-15P

NEMA L7-15P Twist Locking Power Cord - 15A 277V/AC 2P3W, Waterproof Ring Rib
UL/ETL/cULus Certified

NEMA L7-15P twist locking power cord features a 15A 277V/AC rating with 3 prong Male Plug 2 poles 3 wires configuration and Waterproof Ring Rib grip for secure handling. This NEMA L7-15P twist locking Male Plug housing is constructed from flame-retardant, impact-proof material. And all plug prongs are made of 100% copper to deliver superior electrical conductivity and enhanced operational safety. This twist locking plug/connector and power cable with UL, ETL and cULus certified per Standard Designation: UL817 after strict dielectric, continuity and polarity testing. The twist locking power cords mechanism avoids accidental disconnection, ideal for commercial & industrial uses: RV, EV, marine yacht shore power, server racks, medical devices, power tools, indoor/outdoor events, generator adapter cord sets and construction sites. Custom lengths and cables specification can be customized for varied installation. Our NEMA L7-15P twisted locking power cord fully meets global eco regulations including RoHS, REACH, PAHs and California Prop65 standards.

E-mail Now

Specifications

Label	Value
Connector Standard:	NEMA L7-15P
Maximum Current rating:	15A
Maximum Voltage:	277V/AC
Number of Poles and Wires:	3 prong 2 poles 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL/ETL/cULus
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3Cx18AWG	SJ, SJO, SJOW, SJO0, SJOOW, SJE, SJEW, SJE0, SJEOW, SJE00, SJE0OW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, SE, SEW, SEO, SEOW, SEO0, SEOOW, ST, STW, STO, STOW, STOO, STOOW
3Cx16AWG	SJ, SJO, SJOW, SJO0, SJOOW, SJE, SJEW, SJE0, SJEOW, SJE00, SJE0OW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, SE, SEW, SEO, SEOW, SEO0, SEOOW, ST, STW, STO, STOW, STOO, STOOW
3Cx14AWG	SJ, SJO, SJOW, SJO0, SJOOW, SJE, SJEW, SJE0, SJEOW, SJE00, SJE0OW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, SE, SEW, SEO, SEOW, SEO0, SEOOW, ST, STW, STO, STOW, STOO, STOOW
3Cx12AWG	SJ, SJO, SJOW, SJO0, SJOOW, SJE, SJEW, SJE0, SJEOW, SJE00, SJE0OW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, SE, SEW, SEO, SEOW, SEO0, SEOOW, ST, STW, STO, STOW, STOO, STOOW
3Cx10AWG	SJ, SJO, SJOW, SJO0, SJOOW, SJE, SJEW, SJE0, SJEOW, SJE00, SJE0OW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, S, SO, SOW, SOO, SOOW, SE, SEW, SEO, SEOW, SEO0, SEOOW, ST, STW, STO, STOW, STOO, STOOW

Our other certificated products

