



American Twist Locking Power Cords

NEMA SS2-50P Twist Locking Power Cord - 50A 125V/250V 3P4W., Waterproof Shore Power UL/ETL/cULus Certified

Plug and Connector Type: NEMA SS2-50P

NEMA SS2-50P Twist Locking Power Cord - 50A 125V/250V 3P4W, Waterproof Shore Power UL/ETL/cULus Certified

NEMA SS2-50P twist locking power cord features a 50A 125V/250V rating with 4 prong Male Plug 3 poles 4 wires configuration and Waterproof Shore Power grip for secure handling. This NEMA SS2-50P twist locking Male Plug housing is constructed from flame-retardant, impact-proof material. And all plug prongs are made of 100% copper to deliver superior electrical conductivity and enhanced operational safety. This twist locking plug/connector and power cable with UL, ETL and cULus certified per Standard Designation: UL817 after strict dielectric, continuity and polarity testing. The twist locking power cords mechanism avoids accidental disconnection, ideal for commercial & industrial uses: RV, EV, marine yacht shore power, server racks, medical devices, power tools, indoor/outdoor events, generator adapter cord sets and construction sites. Custom lengths and cables specification can be customized for varied installation. Our NEMA SS2-50P twisted locking power cord fully meets global eco regulations including RoHS, REACH, PAHs and California Prop65 standards.

E-mail Now

Specifications

Label	Value
Connector Standard:	NEMA SS2-50P
Maximum Current rating:	50A
Maximum Voltage:	125V/250V
Number of Poles and Wires:	4 prong 3 poles 4 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL/ETL/cULus
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3Cx6AWG+1Cx8AWG	STW, STOW, STOOW, SEOW, SEOOW
4Cx6AWG	STW, STOW, STOOW, SEOW, SEOOW

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Simen Town, Yuyao

Ningbo / Zhejiang, China

315470