



### **30 Amp RV Surge Protector Adapter with Indicator, NEMA TT-30P to NEMA L5-30R**

Plug and Connector Type: NEMA TT-30P Male to NEMA L5-30R Female

This is the same NEMA TT-30P to NEMA L5-30R adapter as the NEMA TT-30P to NEMA L5-30R adapter with the indicator and cover fitted to the housing.

Dockside use is hard on an adapter: salt air, spray and long plugged-in seasons.

The cover protects the socket face when the shore cord is removed, and the LED panel gives a status read without a tester.

**E-mail Now**

## **RV Surge Protector Adapters**

### **Specifications**

| Label                             | Value                                                                        |
|-----------------------------------|------------------------------------------------------------------------------|
| Product Name:                     | 30 Amp RV Surge Protector Adapter with Indicator, NEMA TT-30P to NEMA L5-30R |
| Adapter Type:                     | NEMA TT-30P Male Plug to NEMA L5-30R Female Receptacle                       |
| Male Plug Connector:              | NEMA TT-30P                                                                  |
| Female Receptacle Connector:      | NEMA L5-30R                                                                  |
| Male Plug Current Rating:         | 30A                                                                          |
| Female Receptacle Current Rating: | 30A                                                                          |
| Maximum Current:                  | 30A                                                                          |
| Voltage Rating:                   | 125V                                                                         |
| Prong Configuration:              | 3 prong 2 poles 3 wires                                                      |
| Power Indicator:                  | LED power indicator fitted at the plug end                                   |
| Standard:                         | UL 817                                                                       |
| Safety Approvals:                 | UL, cULus                                                                    |
| Environmental Certifications:     | RoHS, REACH                                                                  |
| Housing Material:                 | PA66 Flame-Retardant Engineering Plastic                                     |
| Contact / Blade Material:         | Nickel-Coated Brass, Pure Copper Conductive Parts                            |
| Flammability Rating:              | UL 94 V-0                                                                    |
| Temperature Rating:               | -40 C to +75 C                                                               |
| Color:                            | Black is standard; any color available on request                            |
| Testing:                          | Hi-Pot (Dielectric Withstand), Polarity (Pinout) and Continuity              |
| Customization:                    | OEM / ODM; custom colors, packaging and labeling available                   |
| Country of Origin:                | Made in China                                                                |
| Packing:                          | Standard Export Carton                                                       |

### **Typical Applications**

For a boat or food truck that stays connected for weeks at a time on a park pedestal, and for anyone who wants the supply verified before the shore cord goes on. Ratings are unchanged: 30A 125V, three wire, UL 817.

### **Before You Plug In**

Rinse and dry the connector faces after saltwater exposure, then check the pins for green corrosion. Corrosion raises resistance at the joint, which is what the heat damage usually starts from.

### **Ordering Notes**

Specify the version with the indicator when both are wanted. The plain NEMA TT-30P to NEMA L5-30R adapter is the same adapter without those fittings.

### **Our other certificated products**



**Yuyao ChengBang**

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: [sales@chinapowercords.com](mailto:sales@chinapowercords.com) <https://www.chinapowercords.com>

Simen Town, Yuyao

Ningbo / Zhejiang, China  
315400