



S, SO, SOW, SOO, SOOW, Rubber Insulated Jacketed Sheathed Flexible Power Cords

USA UL and Canada CSA Standard Rubber Insulated Sheathed Flexible Power Cords

Our S, SO, SOW, SOO, SOOW Power Cable products are fully molded with a low profile ergonomic design and RoHS, REACH and PAHS compliant.

American UL Rubber Power Cables

Specifications

Label	Value
Plug Cables Standard:	UL 62 CSA-C22.2
Number of Wires	2 cores, 3 cores, 4 cores, 5 cores
Rated Voltage:	600V
Rated Temperature:	60°C, 75°C, 90°C, 105°C
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL, CSA Certified List
Environmental Certifications:	RoHS, REACH, PAHS
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

**Simen Town, Yuyao
Ningbo / Zhejiang, China
315470**