



South Africa SABS Power Cords

South africa Power Cords, SANS 164 6A Plug to IEC 60320 C13 Connector, Type D, 3 poles Plug, SABS Certified

Plug and Connector Type: D

South africa SABS 3 pins SANS 164 6A plug to IEC 60320 C13 Connector, South africa Power Supply Cords with SABS Certified List.

Built to SANS 164, IEC 60320 C13 standards.

Rated up to 10A 250V.

South africa Power Cords, 10A 250V, Type D Plug to IEC 60320 C13 Connector. The South africa AC Cords according to SANS 164 6A Standards with SABS certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This South africa Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in South africa market. Our South africa Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

E-mail Now

Specifications

Label	Value
Connector Standard:	SANS 164, IEC 60320 C13
Maximum Current rating:	10A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	SABS
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm ²	H03VV-F
3x0.75mm ²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H
3x1.0mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F
3x1.5mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F

Our other certificated products





Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

**Simen Town, Yuyao
Ningbo / Zhejiang, China
315470**