



Rated up to 10A, 15A, 20A 125V, 250V.

Sun System Grow Light Reflector Ballast Power Cords Sets , 10A, 15A, 20A 125V, 250V, Type Sun System Plug. The Sun System AC Cords according to UL Standards Standards. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This Sun System Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in Sun System market. Our Sun System Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

E-mail Now

Label	Value
Connector Standard:	UL Standards
Maximum Current rating:	10A, 15A, 20A
Maximum Voltage:	125V, 250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL Standards
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Gauge/ # Conductors	Cord Type
3Cx18AWG, 3Cx16AWG	SJT,SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO SOOW, SPT-3, SPT-2, HSJ, HSJO, HSJOO, HSJOW, HSJOOW, 1015
3Cx14AWG, 3Cx12AWG	SJT,SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO SOOW, SPT-3, HSJ, HSJO, HSJOO, HSJOW, HSJOOW, 1015
3Cx10AWG	SJT,SJTW, SJTO, SJTOW, SJTOO, SJTOOW, ST, STW, STO, STOW STOO, STOOW, SJ, SJO, SJOW, SJOO, SJOOW, S, SO, SOW, SOO SOOW, SPT-3, 1015



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

**Simen Town, Yuyao
Ningbo / Zhejiang, China
315470**