



SVT, SVTO, SVTOO, SVT-R, PVC Insulated Jacketed Sheathed Flexible Power Cords

USA UL and Canada CSA Standard PVC Insulated Sheathed Parallel Flexible Power Cords

Our SVT, SVTO, SVTOO, SVT-R Power Cable products are fully molded with a low profile ergonomic design and RoHS, REACH and PAHS compliant.

American UL PVC Power Cables

Specifications

Label	Value
Plug Cables Standard:	UL 62 CSA-C22.2
Number of Wires	2 cores, 3 cores
Rated Voltage:	300V
Rated Temperature:	60°C, 75°C, 90°C, 105°C
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL, CSA Certified List
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Our other certificated products



Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

**Simen Town, Yuyao
Ningbo / Zhejiang, China
315470**