



Swiss SEV Power Cords

Swiss Power Cords, IEC 60320 C14 Connector Plug, Type C14, 3 poles, UL, VDE, TUV, SAA, KC, PSE Certified

Plug and Connector Type: C14

Swiss UL, VDE, TUV, SAA, KC, PSE 3 pins IEC 60320 C14 Connector plug, Swiss Power Supply Cords with UL, VDE, TUV, SAA, KC, PSE Certified List.

Built to IEC 60320 C14 standards.

Rated up to 10A 250V.

Swiss Power Cords, 10A 250V, Type C14 Plug. The Swiss AC Cords according to IEC 60320 C14 Connector Standards with UL, VDE, TUV, SAA, KC, PSE certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This Swiss Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in Swiss market. Our Swiss Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

Specifications

Label	Value
Connector Standard:	IEC 60320 C14
Maximum Current rating:	10A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	UL, VDE, TUV, SAA, KC, PSE
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Available Wire Styles

Gauge/ # Conductors	Cord Type
3x0.5mm ²	H03VV-F
3x0.75mm ²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H, H05V2V2-F
3x1.0mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F, H05V2V2-F
3x1.5mm ²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F

Our other certificated products



Tel: 0086-574-62160227 Fax: 0086-574-62615227
E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

Ningbo / Zhejiang, China
315470