



Thailand Power Cords, 2.5A, 6A, 10A, 16A 250V, Type O Plug to IEC 60320 C13 Connector. The Thailand AC Cords according to TIS 166-2549 Standards with TISI certification. Non-Rewirable Plug 2 poles with Earthing Contact Moulded with Flexible cords. This Thailand Three prong Power Cords match cable for general applications include Flexible cables with thermoplastic PVC Insulation and Flexible cables with crosslinked elastomeric Rubber Insulation in Thailand market. Our Thailand Power Cords Products are fully molded with a low profile ergonomic design and RoHS and Reach compliant.

E-mail Now

Label	Value
Connector Standard:	TIS 166-2549, IEC 60320 C13
Maximum Current rating:	2.5A, 6A, 10A, 16A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	TISI
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

Gauge/ # Conductors	Cord Type
3x0.5mm²	H03VV-F
3x0.75mm²	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H, H05V2V2-F
3x1.0mm²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F, H05V2V2-F
3x1.5mm²	H05VV-F, H05RR-F, H05RN-F, H03RT-H, H07RN-F

Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: sales@chinapowercords.com <https://www.chinapowercords.com>

**Simen Town, Yuyao
Ningbo / Zhejiang, China
315470**