



### Usa Generator Rv Power Splitter Adapter Plug

Plug and Connector Type: NEMA L14-30P Male to NEMA 5-20R Female  
 Usa Generator Rv Power Splitter Adapter Plug with NEMA L14-30P male plug to NEMA 5-20R female socket, manufactured by China Power Cords. This adapter converts NEMA L14-30P (30A 125/250V) to NEMA 5-20R (20A 125V), built with PA66 fire-retardant housing and brass contacts for durable and reliable performance. RoHS, REACH and PAHS compliant with full OEM customization support.

**E-mail Now**

## USA Power Adapter Plugs

### Specifications

| Label                             | Value                                                           |
|-----------------------------------|-----------------------------------------------------------------|
| Product Name:                     | Usa Generator Rv Power Splitter Adapter Plug                    |
| Adapter Type:                     | NEMA L14-30P Male Plug to NEMA 5-20R Female Receptacle          |
| Male Plug Connector:              | NEMA L14-30P                                                    |
| Female Receptacle Connector:      | NEMA 5-20R                                                      |
| Male Plug Current Rating:         | 30A                                                             |
| Female Receptacle Current Rating: | 20A                                                             |
| Male Plug Voltage Rating:         | 125/250V                                                        |
| Female Receptacle Voltage Rating: | 125V                                                            |
| Compatible Regions (Area Served): | United States, Canada, North America                            |
| Housing Material:                 | PA66 Flame-Retardant Engineering Plastic                        |
| Contact / Blade Material:         | Nickel-Coated Brass, Pure Copper Conductive Parts               |
| Flammability Rating:              | UL 94 V-0                                                       |
| Color:                            | Black is standard; any color available on request               |
| Temperature Rating:               | -40 C to +75 C                                                  |
| Safety Approvals:                 | UL, ETL, VDE, TUV (according to configuration)                  |
| Environmental Certifications:     | RoHS, REACH, PAHs, California Prop 65                           |
| Testing:                          | Hi-Pot (Dielectric Withstand), Polarity (Pinout) and Continuity |
| Customization:                    | OEM / ODM; custom colors, packaging and labeling available      |
| Country of Origin:                | Made in China                                                   |
| Packing:                          | Standard Export Carton                                          |

### Our other certificated products



### Yuyao ChengBang

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: [sales@chinapowercords.com](mailto:sales@chinapowercords.com) <https://www.chinapowercords.com>

Simen Town, Yuyao

Ningbo / Zhejiang, China  
 315400