



### **VCTFK, HVCTFK, PVC Insulated Jacketed Sheathed Flexible Power Cords**

Japan PSE Insulated PVC Single Cords

Our VCTFK, HVCTFK Power Cable products are fully molded with a low profile ergonomic design and RoHS, REACH and PAHS compliant.

## **Japan PSE PVC Power Cables**

### **Specifications**

Label	Value
Plug Cables Standard:	JIS C 3306
Number of Wires	2 cores, 3 cores, 4 cores
Rated Voltage:	300V
Rated Temperature:	60°C, 75°C
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Approvals:	PSE Certified List
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity
Packing:	Standard Export Carton

### **Our other certificated products**



**Yuyao ChengBang**

Tel: 0086-574-62160227 Fax: 0086-574-62615227

E-mail: [sales@chinapowercords.com](mailto:sales@chinapowercords.com) <https://www.chinapowercords.com>

**Simen Town, Yuyao  
Ningbo / Zhejiang, China  
315470**